



Key Features

- Highest salt rejection
- Highest boron rejection
- Improved fouling resistance due to thicker feed spacer

Main Benefits

- Best permeate water quality
- Meets high water quality standards with lower system CAPEX requirement

Ideal Applications

- Single-pass SWRO design requiring high permeate water quality



This product is certified to NSF/ANSI/CAN Standard 61 for drinking water systems

D-SW400SRG2-EN-013026

Product Data Sheet

SW 400 SR G2

Industry-leading salt rejection seawater RO membrane delivering the best permeate water quality

- Benefits of NANOH2O SW G2 membrane
- ▶ Better permeate quality without increasing operating pressure
 - ▶ Lower energy costs without reducing permeate quality
 - ▶ Reduced CAPEX and OPEX for multi-pass SWRO systems


Performance Specifications

Item	Unit	Value
Permeate Flow Rate	GPD (m³/d)	6,000 (22.7)
Stabilized Salt Rejection	%	99.89
Minimum Salt Rejection	%	99.75
Stabilized Boron Rejection	%	93
Active Membrane Area	ft² (m²)	400 (37)
Feed Spacer Thickness	mil	34

The specifications outlined above are normalized performances based on the following test conditions:

- Test Condition: 32,000 ppm NaCl, 5 ppm Boron, 800 psi (55.1 bar), 25°C (77°F), pH 8, Recovery 8%
- Permeate flow rates for individual elements may vary by ±15%

Dimensions and Weight



All dimensional information is indicative and for reference only. Please contact The Company for detailed technical specifications.

Operating Specifications

Specification	Unit	Value
Maximum Applied Pressure	psi (bar)	1,200 (82.7)
Maximum Chlorine Concentration	ppm	< 0.1
Maximum Operating Temperature	°C (°F)	45 (113)
pH Range, Continuous Operation		2–11
pH Range, Cleaning		2–13
Maximum Feed Water Turbidity	NTU	1.0
Maximum Feed Water SDI ₁₅		5.0
Maximum Feed Flow	gpm (m³/h)	75 (17)
Maximum Pressure Drop (ΔP) for Each Element	psi (bar)	15 (1.0)

These operating specifications are for general use. For specific applications, operation at more conservative values may ensure better performance and extended membrane life. See The Company Technical Bulletins for more details.

The product performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at The Company web.

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. The Company assumes no liability for results obtained or damages incurred through the application of the information contained

herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. All rights