LG Chem™

Product Data Sheet

SW 4040 R

High-rejection seawater RO membrane for commercial applications

Key Features

- Balanced salt rejection and productivity

Main Benefits

- A combination of excellent water quality and energy efficiency
- Well-proven and long-lasting reliability

Ideal Applications

- Small to medium sized SWRO systems
- Commercial applications

NSF This product is certified to NSF/ANSI/CAN Standard 61 for drinking water systems

D-SW4040R-EN-013026

Performance Specifications

Item	Unit	Value
Permeate Flow Rate	GPD (m^3/d)	1,950 (7.4)
Stabilized Salt Rejection	%	99.7
Minimum Salt Rejection	%	99.5
Active Membrane Area	ft^2 (m^2)	80 (7.4)
Feed Spacer Thickness	mil	28

The specifications outlined above are normalized performances based on the following test conditions:
- Test Conditions: 32,000 ppm NaCl, 5 ppm Boron, 800 psi (55.1 bar), 25°C (77°F), pH 8, Recovery 8%
- Permeate flow rates for individual elements may vary by ±20%

Dimensions and Weight



Dimensions: mm (in)				Wet Weight: kg (lbs)
A	B	C	D	
Element Length	Element O.D.	Core Tube I.D.	Core Tube Ext.	4.2 (9.3)
1,016 (40)	100 (3.9)	19 (0.75)	29 (1.1)	

All dimensional information is indicative and for reference only. Please contact The Company for detailed technical specifications.

Operating Specifications

Specification	Unit	Value
Maximum Applied Pressure	psi (bar)	1,200 (82.)
Maximum Chlorine Concentration	ppm	< 0.1 45
Maximum Operating Temperature	°C (°F)	(113)
pH Range, Continuous Operation		2–11
pH Range, Cleaning		2–13
Maximum Feed Water Turbidity	NTU	1.0
Maximum Feed Water SDI_{15}		5.0
Maximum Feed Flow	gpm (m^3/h)	15 (3.4)
Maximum Pressure Drop (ΔP) for Each Element	psi (bar)	15 (1.0)

These operating specifications are for general use. For specific applications, operation at more conservative values may ensure better performance and extended membrane life. See The Company Technical Bulletins for more details.

The product performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at The Company web.

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. The Company assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. All rights

GLOBAL PROVENTUS

Lázaro Cárdenas #44 Col. Zapata Monterrey N.L. C.P. 64390
T.: (81) 8311- 8181 - www.global-proventus.com
www.membranasparaagua.com - www.osmosisinversa.com.mx