

DuPont™ Inge™ MB 1.5 XL 40 TRS Module

Module for TRS Rack

Key Features

Proven Multibore™ PES Fibers:

- Exceptional physical strength and chemical resistance.
- High colloidal particulate, bacteria and virus log removal rate.
- Unique design for high solids loads.
- Optional coagulation can enhance the removal of algae and organics.

Optimized Module Design:

- Innovative end-cap design to suit TRS Rack concept with simple assembly and scalability.
- Robust materials for long lifetime.
- Easy installation and low maintenance.
- All wetted parts corrosion free.

Key Applications

- Municipal wastewater.
- Industrial water.
- Wastewater reuse.
- Ideal for height restricted or containerized filtration solution.

Module Specification

General


Part Number / GMID	IN-5103 / 12071529
Mode of Filtration	In-Out Pressurized
Membrane Type	Multibore™
Membrane Material	PESm
Nominal Membrane Pore Size	0.02 µm
Module Operating Process	Dead-end
Housing Material	PVC-U, white

Dimensions

Active Membrane Area	40 m²	431 ft²
Module Length Including T-Piece (L)	1,879 mm	74.0 inch
Module Diameter (D)	250 mm	9.8 inch

Weight and Volume

Shipping Weight (Module Only)	47 kg	104 lbs.
Weight Empty (Module and Corresponding Frame)	61 kg	133 lbs.
Weight Filled (Module and Corresponding Frame)	129 kg	284 lbs.
Hold-Up Volume Feed (CIP)	31 L	8.1 gal
Hold-Up Volume Membrane Structure (CIP)	16 L	4.2 gal
Hold-Up Volume Filtrate (CIP)	31 L	8.2 gal



Certified to NSF/ANSI/CAN 61
& NSF/ANSI 419

Form No. 45-D02245-en, Rev. 5
May 2026


Lázaro Cárdenas #44 Col. Zapata Monterrey N.L. C.P. 64390

T.: (81) 8311- 8181 www.membranasparaagua.com - www.osmosisinversa.com.mx

Suggested Operating Conditions

General	Details	
Operating Temperature Range	1 - 45 °C	34 - 113 °F
Operating pH	2 - 12	
Cleaning pH	1 - 13	
Typical Filtration TMP	0.1 - 0.6 bar	1.5 - 8.7 psi
Typical Backwash TMP	0.3 - 2.0 bar	4.4 - 29.0 psi
Backwash Flux	230 L/(m²h)	135 gfd
Backwash Flow	9.2 m³/h	40.5 gpm
Operating Limits (Maximum)		
Rate of Temperature Change	5 °C/min	9 °F/min
Inlet Pressure at max 40°C	5 bar	73 psi
Rate of Pressure Change	0.5 bar/sec	7.3 psi/sec
Filtration TMP	1.5 bar	22 psi
Backwash TMP	3.0 bar	44 psi
Filtration Flux	180 L/(m²h)	106 gfd
Filtration Flow	7.2 m³/h	31.7 gpm
Backwash Flux	300 L/(m²h)	176 gfd
Particle Size	300 µm	
Exposure NaOCl*	≤ 500,000 ppm x h (at pH ≥ 9.5)	
Concentration NaOCl	2,000 ppm	

*NaOCl exposure limits at lower pH are dependent on water type and are project specific.



TRS Rack Configuration

Number of Modules	TRS Rack Unit	Part Number ¹	Length ²		Membrane Area	
			mm	ft	m²	ft²
2 Rows Configuration						
4	TRS-4-2-1	12071170	655	2.15	160	1,722
6	TRS-6-2-1	12071171	985	3.23	240	2,583
8	TRS-8-2-1	12071172	1,315	4.31	320	3,445
10	TRS-10-2-1	12071173	1,645	5.40	400	4,306
12	TRS-12-2-1	12071174	1,975	6.48	480	5,167
14	TRS-14-2-1	12071175	2,305	7.56	560	6,028
16	TRS-16-2-1	12071176	2,635	8.65	640	6,889
18	TRS-18-2-1	12071177	2,965	9.73	720	7,750
20	TRS-20-2-1	12071178	3,295	10.81	800	8,611
22	TRS-22-2-1	12071179	3,625	11.89	880	9,473
24	TRS-24-2-1	12071180	3,955	12.98	960	10,334
26	TRS-26-2-1	12071181	4,285	14.06	1,040	11,195
28	TRS-28-2-1	12071182	4,615	15.14	1,120	12,056
30	TRS-30-2-1	12071183	4,945	16.22	1,200	12,917
32	TRS-32-2-1	12071184	5,275	17.31	1,280	13,778
34	TRS-34-2-1	12071185	5,605	18.39	1,360	14,639
36	TRS-36-2-1	12071186	5,935	19.47	1,440	15,501
38	TRS-38-2-1	12071187	6,265	20.55	1,520	16,362
40	TRS-40-2-1	12071188	6,595	21.64	1,600	17,223

1. Rack parts without modules.

2. Tolerance to ISO 2768-1c.

Form No. 45-D02245-en, Rev. 5
May 2026

Number of Modules	TRS Rack Unit	Part Number ¹	Length ²		Membrane Area	
			mm	ft	m²	ft²
4 Rows Configuration						
16	TRS-16-4-1	12071189	1,315	4.31	640	6,889
20	TRS-20-4-1	12071190	1,645	5.40	800	8,611
24	TRS-24-4-1	12071191	1,975	6.48	960	10,334
28	TRS-28-4-1	12071192	2,305	7.56	1,120	12,056
32	TRS-32-4-1	12071193	2,635	8.65	1,280	13,778
36	TRS-36-4-1	12071194	2,965	9.73	1,440	15,501
40	TRS-40-4-1	12071195	3,295	10.81	1,600	17,223
44	TRS-44-4-1	12071196	3,625	11.89	1,760	18,945
48	TRS-48-4-1	12071197	3,955	12.98	1,920	20,667
52	TRS-52-4-1	12071198	4,285	14.06	2,080	22,390
56	TRS-56-4-1	12071199	4,615	15.14	2,240	24,112
60	TRS-60-4-1	12071200	4,945	16.22	2,400	25,834
64	TRS-64-4-1	12071201	5,275	17.31	2,560	27,557
68	TRS-68-4-1	12071202	5,605	18.39	2,720	29,279
72	TRS-72-4-1	12071203	5,935	19.47	2,880	31,001
76	TRS-76-4-1	12071204	6,265	20.55	3,040	32,723
80	TRS-80-4-1	12071205	6,595	21.64	3,200	34,446

1. Rack parts without modules.

2. Tolerance to ISO 2768-1c.